



Safe / Reliable / Easy to Use



F25-6S/6D



F25-8S/8D



F25-10S/10D

F25-6S/6D model

Weight About 265 g (w/Batteries)
Dimension 156 x 61 x 51 mm (L x W x H)

F25-8S/8D & F25-10S/10D models

Weight About 320 g (w/Batteries)
Dimension 186 x 61 x 51 mm (L x W x H)

Transmitter Unit

- 6 ~ 10 Single / double steps pushbuttons
- Start pushbutton
- Rotary key switch + Emergency stop pushbutton
- Alarm pushbutton (6S/6D Model activated by start pushbutton)

Main Features

Safety Function of "STOP" & "CONTROL"

In accordance with EN ISO 13849-1 Cat. 4

Windows Software

Programmable function setting through PC.

Remote Pairing Technology

To allow instant maintenance on site

Enclosure Durability (Harsh Environment)

Nylon-Fiber made housing for extra shock resistant.

Built-in Alarm System

No need to install extra warning devices

Pre-Wiring Receiver

Receiver pre-installed wire made the installation easy and fast ever.





Receiver Unit

Weight About 1550 g (w/o cable)
Dimension 200 x 162 x 107 mm (L x W x H)

General Spec.

	Operation Frequency	433.05 ~434.79 MHz
	Hamming Distance	≥ 4
	Operation Range	Up to 100 Meters
	Temperature Range	-40°C ~ +85°C
	ID CODE	Over 4.3 billion unique ID code available
Transmitter	Power Supply	4 AA size battery, Alkaline / Rechargeable (NiMH)
	Emission Power	< 10mW
	Power Indication	3-stage with LED indication
Receiver	Power Supply	24 / 48/ 110 / 220 / 380 VAC (50 / 60Hz) ±20%, 12/24 VDC
	Alarm	Built-in horn inside the receiver

ACCESSORIES



Copier



Passive Antenna



TX Protective Case



Battery Charger